



The ultimate strength

Spec

Product Name	G025GC
Size	22inch
Construction Method	Forged 1pc. Wheel Reverse Rim
Safety Standards	5H model: JWL+R Spec 2 6H model: JWL&JWL-T+R Spec 2
Color	Blast Black 2(BT) Shining Light Metal/ Rim FDMC (SI)
Included	No.4 VR CAP MODEL-01 LOW BK/SL (O-Ring)、No.99 VR CAP MODEL-01 LOW DC/SL (O-Ring)、No.56 ET1 AIR VALVE BK
Optional	Vehicle Specific Parts Set

Optional Parts

Vehicle Specific Parts Set



Blast Black 2(BT)



Shining Light Metal/ Rim FDMC (SI)

Prices are noted in Japanese YEN(JPY). Specifications in the English version are intended for customers outside of Japan and do not include Japan sales tax.

SIZE	FACE	INSET (): HUB CLEARANCE (mm)	HOLE	P.C.D.	HUB BORE (φ)	DRILL (φ)	PRICE		CALIPER CLEARANCE	Load (lbs)
							BT COLOR	SI COLOR		
22x9J	F 1	36	5	114.3	73.1	29-15	176,000	181,000	TOYOTA ALPHARD/VELLFIRE(AGH30W)	1,852
		30					-		LEXUS RX450h(GYL25W)/RX350(GGL10W)*	
		35		120	72.6		176,000		TOYOTA ALPHARD/VELLFIRE(40)*	
	F 2	20	6	139.7	106.1				-	2,600
	22x9.5J	F 1	50	6	139.7		106.1	29-15	178,000	183,000
22x10J	F 2	25	5	130	84.1	29-15	180,000	185,000	BENZ G63 AMG G-Class(W463)*	1,852
	F 1	55	6	139.7	106.1				-	2,600

Caution
※CALIPER CLEARANCE are for reference only and do not guarantee inspection, and/or the size mandated by local authorities.
※ * : Tuner size. (Tire and or wheel may interfere or protrude from the body/fender on normal based vehicles.