



FDJ2



Tarmac Black(TBK) (18×9.5J)



Tarmac Black(TBK) (15×5.0J)



Tarmac Black(TBK) (17×6.5J)

MID RACING TR50

Flat-surfaced sports royal 5-spoke

Spec

Product Name	MID RACING TR50
Size	15inch/16inch/17inch/18inch
Construction Method	Cast flow-formed 1-piece wheel (15/16inch are cast 1-piece wheel)
Safety Standards	JWL VIA compliant (6H-139.7 is JWL (800KG) JWLT (955KG) 5H-139.7 is JWLT (620KG) JWLT (700KG) VIA compliant)
Color	Tarmac Black (TBK)
Included	Center cap (except 5-139.7 size) Air valve Sticker
Optional	Center cap ¥3,000 Air valve ¥800

Prices are noted in Japanese YEN(JPY). Specifications in the English version are intended for customers outside of Japan and do not include Japan sales tax.

SIZE	INSET (): HUB CLEARANCE (mm)	HOLE	P.C.D.	HUB BORE (φ)	DRILL (φ)	PRICE		DISK PROTRUSIO N (mm)	Load (lbs)
						TBK COLOR			
15x5J	45(35)	4	100	67.1	29-13		31,000	10.6	1,102
15x7J	35	4	100	67.1	29-13		34,000	-	1,168
16x5.5J	20(35)	5	139.7	108.8	29-13		36,500	-	1,543
16x6J	45(42)	4	100	67.1	29-13		38,000	5.8	1,168
16x6.5J	38(35)	6	139.7	106.1	29-13		39,000	-	2,105
16x7J	35(35)	4	100	67.1	29-13		40,000	-	1,168
17x6.5J	38(35)	6	139.7	106.1	29-13		44,000	-	2,105
17x7.5J	40(51)	5	100	67.1	29-13		46,000	-	1,190
	48(43)		114.3	73.1					1,521
17x9J	22(38)	5	114.3	73.1	29-13		49,000	-	1,521
18x7.5J	50(43)	5	100	67.1	29-13		50,000	-	1,190
18x8J	45(43)	5	114.3	73.1	29-13		50,500	-	1,521

18x8.5J	45(35)	5	100	67.1	29-13	51,000	-	1,190
			120	72.6	29-15			1,587
18x9.5J	22(37)	5	114.3	73.1	29-13	53,000	-	1,521
	12(54)							

Caution

TPMS compatible

This product has the disk protruding beyond the rim depending on the size, so please take care when installing